

## SP-FDS-48SC96LC

### Fiber Optic Termination Box



#### Description

Fiber patch panel is mainly used in the wiring sub-system equipment room or wiring closet, to complete the vertical trunk or building trunk cable termination, connect to LAN network switching equipment, and support fiber cable fixed, splicing and wiring management.

Capacity: 48 SC / 96 LC adapter.

Comply with: ISO / IEC11801 and EN50173 standards.

#### Features

- 1.-Mounted 19" design, fully sealed (2U)
- 2.-Metal structure, the use of high-quality high-strength cold-rolled steel, surface with anti-static spraying treatment, Appearance with clean and beautiful surface
- 3.-Design, with track, to facilitate the construction and future maintenance work
- 4.-New design, can provide 12, 24, 48 FC, ST, SC, LC four interfaces, LC maximum support 96 port
- 5.-Ovide four fiber inlet, ensure the amount of incoming fiber;
- 6.-Ique design of fiber splicing;
- 7.-Ovide empty bracket and bracket with couplers.

#### Parameters

Insertion life: 1000 times

Humidity: 10% to 90% RH

Applicable wire gauge: 22 ~ 24

Rated temperature: -20 ~ 70 °C



#### Measures

W \* H \* D 19"(480mm) \* 3.5"(90mm) \* 13"(330mm)